



BRAKE FLUID DOT 3 SUPER HD

Meets or exceeds Fed. Safety Std No. 116. Exceeds Fed. Spec. VVb680. 284°F minimum wet boiling point. Exceeds S.A.E. Specs. J1703.

BENEFITS: Super heavy duty formula with higher boiling point than conventional DOT 3 brake fluid (450°F) • Recommended for use in disc and drum braking systems

DIRECTIONS: Clean all dirt from around filler plug on master cylinder before removing. FOLLOW VEHICLE MANUFACTURER'S RECOMMENDATIONS WHEN ADDING BRAKE FLUID. REPLACE FILLER PLUG. CHECK FLUID LEVEL ONCE A MONTH. KEEP BRAKE FLUID CLEAN AND DRY. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs. STORE BRAKE FLUID ONLY IN ITS ORIGINAL CONTAINER. KEEP CONTAINER CLEAN AND TIGHTLY CLOSED TO PREVENT ABSORPTION OF MOISTURE. DO NOT REFILL CONTAINER AND DO NOT USE FOR OTHER LIQUIDS. Never wash cylinders or parts with gasoline, kerosene, or oil. Avoid spilling on brake lining or pads or on car finish.

STORAGE, HANDLING & DISPOSAL: Dispose of in accordance with all applicable government laws.

DANGER: DO NOT REFILL CONTAINER AND DO NOT USE FOR OTHER LIQUIDS. Avoid contact with eyes. Wash hands with soap and water properly.

FIRST AID: EYE CONTACT: Flush thoroughly with water for 15 minutes while lifting eyelids occasionally and get prompt medical attention. SKIN CONTACT: Wash with soap and water. If irritation develops or persists, get prompt medical attention. INHALATION: Move to fresh air. If breathing becomes difficult, get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS

M4312	Plastic Bottle, 12 fl. oz. 078698134314
M4332	Plastic Bottle, 32 fl. oz. 078698134321
M4334	Plastic Bottle, 1 gal. 078698134338

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.